




FIRST EARLY DESIGN GUIDANCE OF THE DOWNTOWN DESIGN REVIEW BOARD

Project Number:	3017451
Address:	924 Howell Street
Applicant:	Jim Wescott of Weber Thompson
Date of Meeting:	Tuesday, September 02, 2014
Board Members Present:	Anjali Grant Murphy McCullough Alan McWain
Board Members Absent:	Mathew Albores Gundula Proksch
DPD Staff Present:	Bruce P. Rips

SITE & VICINITY

Site Zone: Downtown Mixed Commercial with height limits ranging between 290 and 400 feet depending upon the land use. (DMC 340/290-400)

Nearby Zones: The DMC 340/290-400 zone extends south from Howell St toward I-5 and north to Virginia Street. West of Ninth Avenue the zoning classification changes to Downtown Office Commercial with a range in height of 300 to 500 feet (DOC2 500/300-500) depending upon use. East of Boren Avenue the zoning is also DMC with height ranges of 240 to 400 feet. This zone continues northwestward toward Denny Way.



Lot Area: The three parcels contain a total of 21,000 sq. ft. Located at the northwest corner of Terry Ave and Howell St, the site occupies the southeast portion of the block. The site has 180' of frontage along Terry Ave and 120' of frontage along Howell St. It lies at the gridline shift along Howell St and marks the edge of Terry Ave as one approaches the future convention center expansion site. The site has approximately a four foot declension from the height point at the corner of Terry and Howell to the northwest.

Current Development: The property contains a principal use surface parking lot.

Surrounding Development and Neighborhood Character: With the Denny Triangle area of downtown, the site borders the 37- story Aspira residential tower. Across the alley lies the 15- story, Regence Blue Shield tower and a mixed use building containing Gethsemane Lutheran Church, Hope Center and Compass Housing apartments. Across Terry Ave to the east at 1800 Howell St. is a five-story storage building with a master use permit for a residential tower. On the Williamsburg Apartments site at Stewart St. and Terry Ave, a proposal calls for a 14-story office tower. Further east, a two building complex under construction called Hill 7 will contain an office building and a hotel. North of Stewart St. Seattle Children’s Research Institute is adding to their campus.

The vicinity contains a mix of commercial and residential structures of various styles and eras. Overall they generate a consistently pedestrian friendly public realm. The area to the south and west is characterized by more recent, very high density towers, while to the north and northeast is mostly parking lots and low commercial buildings. A potential expansion of the convention center might occur one block to the south.

Access: Howell Street (one-way, principal arterial), Terry Avenue (one-way Green Street) and an alley border the site.

Environmentally Critical Areas: There are no mapped environmental critical areas.

PROJECT DESCRIPTION: The applicant proposes a 17-story, 307 room hotel with ground level restaurant, retail and a 220-230 space parking garage provided above and below grade.

DESIGN DEVELOPMENT

The hotel program varied little in the schemes presented at the EDG meeting with ground floor entry and lobby fronting on Terry Ave, dining area (undetermined whether this would be a full service restaurant) at the corner of Howell St. and Terry Ave, a retail component along Howell and back of house services including loading and garage access from the alley. Parking garages, separated by the first floor, occupy two levels below grade and two levels above grade. Meeting rooms and a guest amenity area comprise most of the fourth floor. Floors five through 17 contain guest rooms.

Prior to the meeting, the applicant provided three massing schemes: a “C” shaped mass facing Terry Ave. raised above a four story plinth; its inverse with the open area or court facing west toward the alley; and a “L” scheme with the wings fronting Terry Ave and Howell St. In the latter scheme, the bulk of the Terry Ave mass sets back above 45 feet on Terry (partially meeting the Green St. requirement), leaving a four-story plinth for the ground floor and the above grade parking garage. The Howell St. façade approaches the right of way. Additional drawings illustrate an angled volume occupying the corner. In appearance, the mass has three major elements: a four story plinth articulated by large vertical frames along Terry and Howell, the

hotel wings above the parking and ground floor plinth and a vertical tower set at an angle from the street grid emphasizing the corner. The top of the tower, housing mechanical rooms, rises above the two wings.

At the EDG meeting, the architect supplied the Board with a new version of the third scheme (this was not posted on the DPD web site). This scheme eliminates the upper level parking freeing the first floor of an additional ramp and moves the meeting/amenity area to the second floor. Its impact on the massing occurs at the plinth. The corner volume has a terrace at the second level drawing greater visual interest near the two streets. The plinth with its frames drops in height along Howell St.

A significant issue is vehicular access to the proposed hotel. The applicant prefers a two-way 25' curb cut on the Terry Ave Green Street and a wide driveway from Terry to the alley to accommodate loading and access to one of the two ramps to the parking garage. Several alternatives were presented in the EDG booklet 1) a no curb cut option with a lay-by or vehicular pull out lane on Terry Ave., 2) a Howell Street scheme (oddly configured), and 3) a 16' one-way curb cut on Terry.

DPD Senior Urban Designer Lyle Bicknell spoke about maintaining the integrity of the Terry Ave Green St. and the pedestrian safety. Representing DPD and voicing sentiments raised by SDOT after reviewing material produced by the applicant, Lyle urged an alternative to placing a curb cut on the green street.

PUBLIC COMMENT

Two members of the public affixed their names to the EDG meeting sign-in sheet. A speaker commented on the following issues.

- The alley is heavily trafficked. Consider angled parking at the loading dock.
- The roof top is an important design element as neighbors will look at it.
- Review the impacts of the roof top mechanical systems on the Aspira residents. Consider the appearance and materials used for the mechanical systems.

PRIORITIES & BOARD RECOMMENDATIONS

After visiting the site, considering the analysis of the site and context provided by the proponents, and hearing public comment, the Design Review Board members provided the following siting and design guidance.

DESIGN REVIEW GUIDELINES

The priority Citywide and Neighborhood guidelines identified by the Board as Priority Guidelines are summarized below, while all guidelines remain applicable. For the full text please visit the [Design Review website](#).

SITE PLANNING AND MASSING

A1 Respond to the Physical Environment: Develop an architectural concept and compose the building's massing in response to geographic conditions and patterns of urban form found nearby or beyond the immediate context of the building site.

A1.1. Response to Context: Each building site lies within a larger physical context having various and distinct features and characteristics to which the building design should respond. Develop an architectural concept and arrange the building mass in response to one or more of the following, if present:

- a. a change in street grid alignment that yields a site having nonstandard shape;
- b. a site having dramatic topography or contrasting edge conditions;
- c. patterns of urban form, such as nearby buildings that have employed distinctive and effective massing compositions;
- d. access to direct sunlight—seasonally or at particular times of day;
- e. views from the site of noteworthy structures or natural features, (i.e.: the Space Needle, Smith Tower, port facilities, Puget Sound, Mount Rainier, the Olympic Mountains);
- f. views of the site from other parts of the city or region; and
- g. proximity to a regional transportation corridor (the monorail, light rail, freight rail, major arterial, state highway, ferry routes, bicycle trail, etc.).

A1.2. Response to Planning Efforts: Some areas downtown are transitional environments, where existing development patterns are likely to change. In these areas, respond to the urban form goals of current planning efforts, being cognizant that new development will establish the context to which future development will respond.

A2 Enhance the Skyline: Design the upper portion of the building to promote visual interest and variety in the downtown skyline. Respect existing landmarks while responding to the skyline's present and planned profile.

A2.1. Desired Architectural Treatments: Use one or more of the following architectural treatments to accomplish this goal:

- a. sculpt or profile the facades;
- b. specify and compose a palette of materials with distinctive texture, pattern, or color;
- c. provide or enhance a specific architectural rooftop element.

A2.2. Rooftop Mechanical Equipment: In doing so, enclose and integrate any rooftop mechanical equipment into the design of the building as a whole.

Responding to the public comment urging a well-designed roof, the Board noted that neighbors would look down on the mechanical systems. This presented sufficient reason to create an attractive enclosure housing the HVAC and other mechanical equipment.

ARCHITECTURAL EXPRESSION

B1 Respond to the neighborhood context: Develop an architectural concept and compose the major building elements to reinforce desirable urban features existing in the surrounding neighborhood.

B1.1. Adjacent Features and Networks: Each building site lies within an urban neighborhood context having distinct features and characteristics to which the building design should respond.

Arrange the building mass in response to one or more of the following, if present:

- a. a surrounding district of distinct and noteworthy character;
- b. an adjacent landmark or noteworthy building;
- c. a major public amenity or institution nearby;
- d. neighboring buildings that have employed distinctive and effective massing compositions;
- e. elements of the pedestrian network nearby, (i.e.: green street, hillclimb, mid-block crossing, through-block passageway); and
- f. direct access to one or more components of the regional transportation system.

B1.2. Land Uses: Also, consider the design implications of the predominant land uses in the area surrounding the site.

B2 Create a Transition in Bulk and Scale: Compose the massing of the building to create a transition to the height, bulk, and scale of development in nearby less-intensive zones.

B2.1. Analyzing Height, Bulk, and Scale: Factors to consider in analyzing potential height, bulk, and scale impacts include:

- a. topographic relationships;
- b. distance from a less intensive zone edge;
- c. differences in development standards between abutting zones (allowable building height, width, lot coverage, etc.);
- d. effect of site size and shape;
- e. height, bulk, and scale relationships resulting from lot orientation (e.g., back lot line to back lot line vs back lot line to side lot line); and
- f. type and amount of separation between lots in the different zones (e.g., separation by only a property line, by an alley or street, or by other physical features such as grade changes); g. street grid or platting orientations.

B2.2. Compatibility with Nearby Buildings: In some cases, careful siting and design treatment may be sufficient to achieve reasonable transition and mitigation of height, bulk, and scale impacts. Some techniques for achieving compatibility are as follows:

- h. use of architectural style, details (such as roof lines, beltcourses, cornices, or fenestration), color, or materials that derive from the less intensive zone.
- i. architectural massing of building components; and
- j. responding to topographic conditions in ways that minimize impacts on neighboring development, such as by stepping a project down the hillside.

B2.3. Reduction of Bulk: In some cases, reductions in the actual bulk and scale of the proposed structure may be necessary in order to mitigate adverse impacts and achieve an acceptable level of compatibility. Some techniques which can be used in these cases include:

- k. articulating the building's facades vertically or horizontally in intervals that reflect to existing structures or platting pattern;
- l. increasing building setbacks from the zone edge at ground level;
- m. reducing the bulk of the building's upper floors; and
- n. limiting the length of, or otherwise modifying, facades.

B3 Reinforce the Positive Urban Form & Architectural Attributes of the Immediate Area.: Consider the predominant attributes of the immediate neighborhood and reinforce desirable siting patterns, massing arrangements, and streetscape characteristics of nearby development.

B3.1. Building Orientation: In general, orient the building entries and open space toward street intersections and toward street fronts with the highest pedestrian activity. Locate parking and vehicle access away from entries, open space, and street intersections considerations.

B3.2. Features to Complement: Reinforce the desirable patterns of massing and facade composition found in the surrounding area. Pay particular attention to designated landmarks and other noteworthy buildings. Consider complementing the existing:

- a. massing and setbacks,
- b. scale and proportions,
- c. expressed structural bays and modulations,
- d. fenestration patterns and detailing,
- e. exterior finish materials and detailing,
- f. architectural styles, and
- g. roof forms.

B3.3. Pedestrian Amenities at the Ground Level: Consider setting the building back slightly to create space adjacent to the sidewalk conducive to pedestrian-oriented activities such as vending, sitting, or dining. Reinforce the desirable streetscape elements found on adjacent blocks. Consider complementing existing:

- h. public art installations,
- i. street furniture and signage systems,
- j. lighting and landscaping, and
- k. overhead weather protection.

B4 Design a Well-Proportioned & Unified Building: Compose the massing and organize the interior and exterior spaces to create a well-proportioned building that exhibits a coherent architectural concept. Design the architectural elements and finish details to create a unified building, so that all components appear integral to the whole.

B4.1. Massing: When composing the massing, consider how the following can contribute to create a building that exhibits a coherent architectural concept:

- a. setbacks, projections, and open space;

- b. relative sizes and shapes of distinct building volumes; and
- c. roof heights and forms.

The Board prefers the ‘massing’ of the “Alternative Scheme” with its oblique corner and the void or cut-out at the second level overlooking the intersection. Consider redesigning the corner’s angle to enhance its obliqueness and place a greater portion of this volume back within the required green street setback in order to reduce the amount of cubic area requiring a departure request. Work on revising the tower’s proportions to produce a more slender and refined corner tower. From some angles, its mass overwhelms the anchoring provided by the Howell St. façade.

B4.2. Coherent Interior/Exterior Design: When organizing the interior and exterior spaces and developing the architectural elements, consider how the following can contribute to create a building that exhibits a coherent architectural concept:

- d. facade modulation and articulation;
- e. windows and fenestration patterns;
- f. corner features;
- g. streetscape and open space fixtures;
- h. building and garage entries; and
- i. building base and top.

The frames delineating the podium appear ponderous and inelegant to the pedestrian’s scale. Covering the upper level parking garage apertures with green screen is an insufficient response to an important design issue. The Board recommended that the architect study the elegant solution of an above grade parking garage integrated within a podium proposed at Western and University (project # 3014451).

The Board prefers an active second floor as programmed in the alternative scheme. The lack of an above-grade garage would not justify a curb-cut on Terry Ave as the two elements are unrelated. (Staff note: the 220-230 parking spaces represent a significantly greater number of spaces than a downtown hotel (even with a restaurant and a small retail space) typically warrants. The Land Use Code requires one space per four hotel rooms.)

B4.3. Architectural Details: When designing the architectural details, consider how the following can contribute to create a building that exhibits a coherent architectural concept:

- j. exterior finish materials;
- k. architectural lighting and signage;
- l. grilles, railings, and downspouts;
- m. window and entry trim and moldings;
- n. shadow patterns; and
- o. exterior lighting.

How does the podium wrap-back into the larger volume? The condition illustrated on p. 68 of the alternative scheme needs better articulation along with the rest of the framing device.

THE STREETScape

C1 Promote Pedestrian Interaction: Spaces for street level uses should be designed to engage pedestrians with the activities occurring within them. Sidewalk-related spaces should appear safe, welcoming, and open to the general public.

C1.1. Street Level Uses: Provide spaces for street level uses that:

- a. reinforce existing retail concentrations;
- b. vary in size, width, and depth;
- c. enhance main pedestrian links between areas; and
- d. establish new pedestrian activity where appropriate to meet area objectives. Design for uses that are accessible to the general public, open during established shopping hours, generate walk-in pedestrian clientele, and contribute to a high level of pedestrian activity.

C1.2. Retail Orientation: Where appropriate, consider configuring retail space to attract tenants with products or services that will “spill-out” onto the sidewalk (up to six feet where sidewalk is sufficiently wide).

C1.3. Street-Level Articulation for Pedestrian Activity: Consider setting portions of the building back slightly to create spaces conducive to pedestrian-oriented activities such as vending, resting, sitting, or dining. Further articulate the street level facade to provide an engaging pedestrian experience via:

- e. open facades (i.e., arcades and shop fronts);
- f. multiple building entries;
- g. windows that encourage pedestrians to look into the building interior;
- h. merchandising display windows;
- i. street front open space that features art work, street furniture, and landscaping;
- j. exterior finish materials having texture, pattern, lending themselves to high quality detailing.

C2 Design Facades of Many Scales: Design architectural features, fenestration patterns, and material compositions that refer to the scale of human activities contained within. Building facades should be composed of elements scaled to promote pedestrian comfort, safety, and orientation.

C2.1. Modulation of Facades: Consider modulating the building facades and reinforcing this modulation with the composition of:

- a. the fenestration pattern;
- b. exterior finish materials;
- c. other architectural elements;
- d. light fixtures and landscaping elements; and
- e. the roofline.

See discussion of the corner tower in Guidance B4.1.

C3 Provide Active — Not Blank — Facades: Buildings should not have large blank walls facing the street, especially near sidewalks.

C3.1. Desirable Facade Elements: Facades which for unavoidable programmatic reasons may have few entries or windows should receive special design treatment to increase pedestrian safety, comfort, and interest. Enliven these facades by providing:

- a. small retail spaces (as small as 50 square feet) for food bars, newstands, and other specialized retail tenants;
- b. visibility into building interiors;
- c. limited lengths of blank walls;
- d. a landscaped or raised bed planted with vegetation that will grow up a vertical trellis or frame installed to obscure or screen the wall's blank surface;
- e. high quality public art in the form of a mosaic, mural, decorative masonry pattern, sculpture, relief, etc., installed over a substantial portion of the blank wall surface;
- f. small setbacks, indentations, or other architectural means of breaking up the wall surface;
- g. different textures, colors, or materials that break up the wall's surface.
- h. special lighting, a canopy, awning, horizontal trellis, or other pedestrian-oriented feature to reduce the expanse of the blank surface and add visual interest;
- i. seating ledges or perches (especially on sunny facades and near bus stops);
- j. merchandising display windows or regularly changing public information display cases.

C4 Reinforce Building Entries: To promote pedestrian comfort, safety, and orientation, reinforce building entries.

C4.1. Entry Treatments: Reinforce the building's entry with one or more of the following architectural treatments:

- a. extra-height lobby space;
- b. distinctive doorways;
- c. decorative lighting;
- d. distinctive entry canopy;
- e. projected or recessed entry bay;
- f. building name and address integrated into the facade or sidewalk;
- g. artwork integrated into the facade or sidewalk;
- h. a change in paving material, texture, or color;
- i. distinctive landscaping, including plants, water features and seating
- j. ornamental glazing, railings, and balustrades.

C4.2. Residential Entries: To make a residential building more approachable and to create a sense of association among neighbors, entries should be clearly identifiable and visible from the street and easily accessible and inviting to pedestrians. The space between the building and the sidewalk should provide security and privacy for residents and encourage social interaction among residents and neighbors. Provide convenient and attractive access to the building's entry. To ensure comfort and security, entry areas and adjacent open space should be sufficiently

lighted and protected from the weather. Opportunities for creating lively, pedestrian-oriented open space should be considered.

C5 Encourage Overhead Weather Protection: Project applicants are encouraged to provide continuous, well-lit, overhead weather protection to improve pedestrian comfort and safety along major pedestrian routes.

C5.1. Overhead Weather Protection Design Elements: Overhead weather protection should be designed with consideration given to:

- a. the overall architectural concept of the building
- b. uses occurring within the building (such as entries and retail spaces) or in the adjacent streetscape environment (such as bus stops and intersections);
- c. minimizing gaps in coverage;
- d. a drainage strategy that keeps rain water off the street-level facade and sidewalk;
- e. continuity with weather protection provided on nearby buildings;
- f. relationship to architectural features and elements on adjacent development, especially if abutting a building of historic or noteworthy character;
- g. the scale of the space defined by the height and depth of the weather protection;
- h. use of translucent or transparent covering material to maintain a pleasant sidewalk environment with plenty of natural light; and
- i. when opaque material is used, the illumination of light-colored undersides to increase security after dark.

The Board requested continuous canopies along the two major facades. Give better shape and definition to the canopy at the corner volume. Its outer edge doesn't necessarily need to run parallel to the two planes of the tower.

C6 Develop the Alley Façade: To increase pedestrian safety, comfort, and interest, develop portions of the alley facade in response to the unique conditions of the site or project.

C6.1. Alley Activation: Consider enlivening and enhancing the alley entrance by:

- a. extending retail space fenestration into the alley one bay;
- b. providing a niche for recycling and waste receptacles to be shared with nearby, older buildings lacking such facilities; and
- c. adding effective lighting to enhance visibility and safety.

C6.2. Alley Parking Access: Enhance the facades and surfaces in and adjacent to the alley to create parking access that is visible, safe, and welcoming for drivers and pedestrians. Consider

- d. locating the alley parking garage entry and/ or exit near the entrance to the alley;
- e. installing highly visible signage indicating parking rates and availability on the building facade adjacent to the alley; and
- f. chamfering the building corners to enhance pedestrian visibility and safety where alley is regularly used by vehicles accessing parking and loading.

The alley should be more thoroughly explored as an entry approach for drop-off for the hotel. The porte-cochere could sit parallel to the alley. Enhancements to the alley, with pavers, festival and other types of lighting and an attractive façade, could produce a strong and convincing sense of place in the spirit of Hotel 1000 at First Ave and Madison and The Olivian (apartment building) at Eighth Ave and Olive Way.

PUBLIC AMENITIES

D1 Provide Inviting & Usable Open Space: Design public open spaces to promote a visually pleasing, safe, and active environment for workers, residents, and visitors. Views and solar access from the principal area of the open space should be especially emphasized.

D1.1. Pedestrian Enhancements: Where a commercial or mixed-use building is set back from the sidewalk, pedestrian enhancements should be considered in the resulting street frontage. Downtown the primary function of any open space between commercial buildings and the sidewalk is to provide access into the building and opportunities for outdoor activities such as vending, resting, sitting, or dining.

- a. All open space elements should enhance a pedestrian oriented, urban environment that has the appearance of stability, quality, and safety.
- b. Preferable open space locations are to the south and west of tower development, or where the siting of the open space would improve solar access to the sidewalk.
- c. Orient public open space to receive the maximum direct sunlight possible, using trees, overhangs, and umbrellas to provide shade in the warmest months. Design such spaces to take advantage of views and solar access when available from the site.
- d. The design of planters, landscaping, walls, and other street elements should allow visibility into and out of the open space.

D1.2. Open Space Features: Open spaces can feature art work, street furniture, and landscaping that invite customers or enhance the building's setting. Examples of desirable features to include are:

- a. visual and pedestrian access (including barrier-free access) into the site from the public sidewalk;
- b. walking surfaces of attractive pavers;
- c. pedestrian-scaled site lighting;
- d. retail spaces designed for uses that will comfortably "spill out" and enliven the open space;
- e. areas for vendors in commercial areas;
- f. landscaping that enhances the space and architecture;
- g. pedestrian-scaled signage that identifies uses and shops; and
- h. site furniture, art work, or amenities such as fountains, seating, and kiosks. residential open space

D2 Enhance the Building with Landscaping: Enhance the building and site with generous landscaping— which includes special pavements, trellises, screen walls, planters, and site furniture, as well as living plant material.

D2.1. Landscape Enhancements: Landscape enhancement of the site may include some of the approaches or features listed below:

- a. emphasize entries with special planting in conjunction with decorative paving and/or lighting;
- b. include a special feature such as a courtyard, fountain, or pool;
- c. incorporate a planter guard or low planter wall as part of the architecture;
- d. distinctively landscape open areas created by building modulation;
- e. soften the building by screening blank walls, terracing retaining walls, etc;
- f. increase privacy and security through screening and/or shading;
- g. provide a framework such as a trellis or arbor for plants to grow on;
- h. incorporate upper story planter boxes or roof planters;
- i. provide identity and reinforce a desired feeling of intimacy and quiet;
- j. provide brackets for hanging planters;
- k. consider how the space will be viewed from the upper floors of nearby buildings as well as from the sidewalk; and
- l. if on a designated Green Street, coordinate improvements with the local Green Street plan.

D2.2. Consider Nearby Landscaping: Reinforce the desirable pattern of landscaping found on adjacent block faces.

- m. plant street trees that match the existing planting pattern or species;
- n. use similar landscape materials; and
- o. extend a low wall, use paving similar to that found nearby, or employ similar stairway construction methods.

The developers of the 1007 Stewart project (MUP 3016095) on the Williamsburg Apartment site will fund Green Street improvements along the entirety of this block of Terry Ave with the exception of the improvements already in place at the Aspira. For the Recommendation meeting, show all existing and proposed right of way improvements along this breadth of Terry Ave.

D3 Provide Elements That Define the Place: Provide special elements on the facades, within public open spaces, or on the sidewalk to create a distinct, attractive, and memorable “sense of place” associated with the building.

D3.1. Public Space Features and Amenities: Incorporate one or more of the following appropriate:

- a. public art;
- b. street furniture, such as seating, newspaper boxes, and information kiosks;
- c. distinctive landscaping, such as specimen trees and water features;
- d. retail kiosks;
- e. public restroom facilities with directional signs in a location easily accessible to all; and

f. public seating areas in the form of ledges, broad stairs, planters and the like, especially near public open spaces, bus stops, vending areas, on sunny facades, and other places where people are likely to want to pause or wait.

D3.2. Intersection Focus: Enliven intersections by treating the corner of the building or sidewalk with public art and other elements that promote interaction (entry, tree, seating, etc.) and reinforce the distinctive character of the surrounding area.

D4 Provide Appropriate Signage: Design signage appropriate for the scale and character of the project and immediate neighborhood. All signs should be oriented to pedestrians and/or persons in vehicles on streets within the immediate neighborhood.

D4.1. Desired Signage Elements: Signage should be designed to:

- a. facilitate rapid orientation
- b. add interest to the street level environment
- c. reduce visual clutter
- d. unify the project as a whole
- e. enhance the appearance and safety of the downtown area.

D4.2. Unified Signage System: If the project is large, consider designing a comprehensive building and tenant signage system using one of the following or similar methods:

- a. signs clustered on kiosks near other street furniture or within sidewalk zone closest to building face;
- b. signs on blades attached to building facade;
- c. signs hanging underneath overhead weather protection.

D4.3. Signage Types: Also consider providing:

- d. building identification signage at two scales: small scale at the sidewalk level for pedestrians, and large scale at the street sign level for drivers;
- e. sculptural features or unique street furniture to complement (or in lieu of) building and tenant signage;
- f. interpretive information about building and construction activities on the fence surrounding the construction site.

D4.4. Discourage Upper-Level Signage: Signs on roofs and the upper floors of buildings intended primarily to be seen by motorists and others from a distance are generally discouraged.

D5 Provide Adequate Lighting: To promote a sense of security for people downtown during nighttime hours, provide appropriate levels of lighting on the building facade, on the underside of overhead weather protection, on and around street furniture, in merchandising display windows, in landscaped areas, and on signage.

D5.1. Lighting Strategies: Consider employing one or more of the following lighting strategies as appropriate.

- a. Illuminate distinctive features of the building, including entries, signage, canopies, and areas of architectural detail and interest.
- b. Install lighting in display windows that spills onto and illuminates the sidewalk.
- c. Orient outside lighting to minimize glare within the public right-of-way.

D6 Design for Personal Safety & Security: Design the building and site to promote the feeling of personal safety and security in the immediate area.

D6.1. Safety in Design Features: To help promote safety for the residents, workers, shoppers, and visitors who enter the area:

- a. provide adequate lighting;
- b. retain clear lines of sight into and out of entries and open spaces;
- c. use semi-transparent security screening, rather than opaque walls, where appropriate;
- d. avoid blank and windowless walls that attract graffiti and that do not permit residents or workers to observe the street;
- e. use landscaping that maintains visibility, such as short shrubs and/or trees pruned so that all branches are above head height;
- f. use ornamental grille as fencing or over ground-floor windows in some locations;
- g. avoid architectural features that provide hiding places for criminal activity;
- h. design parking areas to allow natural surveillance by maintaining clear lines of sight for those who park there, for pedestrians passing by, and for occupants of nearby buildings;
- i. install clear directional signage;
- j. encourage “eyes on the street” through the placement of windows, balconies, and street-level uses; and
- k. ensure natural surveillance of children’s play areas.

VEHICULAR ACCESS AND PARKING

E1 Minimize Curb Cut Impacts: Minimize adverse impacts of curb cuts on the safety and comfort of pedestrians.

E1.1. Vehicle Access Considerations: Where street access is deemed appropriate, one or more of the following design approaches should be considered for the safety and comfort of pedestrians.

- a. minimize the number of curb cuts and locate them away from street intersections;
- b. minimize the width of the curb cut, driveway, and garage opening;
- c. provide specialty paving where the driveway crosses the sidewalk;
- d. share the driveway with an adjacent property owner;
- e. locate the driveway to be visually less dominant;
- f. enhance the garage opening with specialty lighting, artwork, or materials having distinctive texture, pattern, or color
- g. provide sufficient queueing space on site.

E1.2. Vehicle Access Location: Where possible, consider locating the driveway and garage entrance to take advantage of topography in a manner that does not reduce pedestrian safety nor place the pedestrian entrance in a subordinate role.

See Board guidance for C6.2.

E2 Integrate Parking Facilities: Minimize the visual impact of parking by integrating parking facilities with surrounding development. Incorporate architectural treatments or suitable

landscaping to provide for the safety and comfort of people using the facility as well as those walking by.

E2.1. Parking Structures: Minimize the visibility of at-grade parking structures or accessory parking garages. The parking portion of a structure should be architecturally compatible with the rest of the building and streetscape. Where appropriate consider incorporating one or more of the following treatments:

- a. Incorporate pedestrian-oriented uses at street level to reduce the visual impact of parking structures. A depth of only 10 feet along the front of the building is sufficient to provide space for newsstands, ticket booths, flower shops, and other viable uses.
- b. Use the site topography to help reduce the visibility of the parking facility.
- c. Set the parking facility back from the sidewalk and install dense landscaping.
- d. Incorporate any of the blank wall treatments listed in Guideline C-3.
- e. Visually integrate the parking structure with building volumes above, below, and adjacent.
- f. Incorporate artwork into the facades.
- g. Provide a frieze, cornice, canopy, overhang, trellis or other device at the top of the parking level.
- h. Use a portion of the top of the parking level as an outdoor deck, patio, or garden with a rail, bench, or other guard device around the perimeter.

E2.2. Parking Structure Entrances: Design vehicular entries to parking structure so that they do not dominate the street frontage of a building. Subordinate the garage entrance to the pedestrian entrance in terms of size, prominence on the street-scape, location, and design emphasis. Consider one or more of the following design strategies:

- i. Enhance the pedestrian entry to reduce the relative importance of the garage entry.
- j. Recess the garage entry portion of the facade or extend portions of the structure over the garage entry to help conceal it.
- k. Emphasize other facade elements to reduce the visual prominence of the garage entry.
- l. Use landscaping or artwork to soften the appearance of the garage entry from the street.
- m. Locate the garage entry where the topography of the site can help conceal it.

E3 Minimize the Presence of Service Areas: Locate service areas for trash dumpsters, loading docks, mechanical equipment, and the like away from the street front where possible. Screen from view those elements which for programmatic reasons cannot be located away from the street front.

E3.1. Methods of Integrating Service Areas: Consider incorporating one or more of the following to help minimize these impacts:

- a. Plan service areas for less visible locations on the site, such as off the alley.
- b. Screen service areas to be less visible.
- c. Use durable screening materials that complement the building.
- d. Incorporate landscaping to make the screen more effective.
- e. Locate the opening to the service area away from the sidewalk.

Consider angling the loading berths as suggested by a member of the public.

DEVELOPMENT STANDARD DEPARTURES

At the time of the Final Early Design Guidance meeting the following departures were requested:

1. SMC 23.49.058F.2 Upper Level Setbacks. The Code requires when a lot in a DMC zone is located on a designated green street, a continuous upper-level setback of 15 feet shall be provided on the street frontage abutting the green street at a height of 45 feet.

The applicant proposes to extend the corner volume at Howell St and Terry Ave ten feet over the required setback.

Board guidance for B4.1 indicated an interest in an oblique angled corner; however, the amount of volume projecting into the Green Street setback should be reduced by angling a portion of the corner back within the setback. The applicant will need to calculate the total cubic volume exceeding the Green St. setback for the next meeting.

2. SMC 23.49.018D. Overhead Weather Protection. Land Use Code states that the lower edge of overhead weather protection must be a minimum ten feet and a maximum 15 feet above the sidewalk grade.

The applicant proposes to lift the canopy between 16 and 18 feet above sidewalk grade.

The Board will consider a higher canopy but the design needs improvement. The canopy on the building should be continuous, have greater depth and the corner canopy expressed differently. See guidance for C5.1.

3. SMC 23.54.030D.3. Driveway Standards. The Land Use Code requires that no driveway slope shall exceed 15 percent except as provided in subsection 23.54.030D.3

The applicant proposes driveway slopes for the garage of 20 percent.

The Board indicated that it had no strong preference regarding the slope of the ramp.

BOARD DIRECTION

At the conclusion of the Final Early Design Guidance meeting, the Board recommended moving forward to MUP application.

The packet includes materials presented at the meeting, and is available online by entering the project number at this website:

http://www.seattle.gov/dpd/Planning/Design_Review_Program/Project_Reviews/Reports/default.asp.

The packet is also available to view in the file, by contacting the Public Resource Center at DPD:

Mailing Public Resource Center

Address: 700 Fifth Ave., Suite 2000

P.O. Box 34019

Seattle, WA 98124-4019

Email: PRC@seattle.gov

Ripsb/doc/design review/EDG.3017451.docx