



**EARLY DESIGN GUIDANCE OF THE
WEST DESIGN REVIEW BOARD**

Record Number: 3035104-EG
Address: 222 5th Ave N
Applicant: Scott Waggoner, Gensler
Date of Meeting: Wednesday, February 05, 2020
Board Members Present: Stephen Porter (chair)
Gloria Mah
Jen Montessoro
Brian Walters
Board Members Absent: Patreese Martin
John Morefield
SDCI Staff Present: Allison Whitworth

SITE & VICINITY

Site Zone: SM-UP 160 (M)
Nearby Zones: (North) SM-UP 95 (M)
(South) DMR/R 145/65
(East) SM-SLU 175/85-280
(West) SM-UP 95 (M)
Lot Area: 25,495 sq. ft.



Current Development:

The subject site is comprised of two existing tax parcels currently developed with a restaurant constructed in 1980 and a surface parking lot. The site slopes downward approximately six feet from south to north.

Surrounding Development and Neighborhood Character:

The project site is located at the southeast corner of 5th Ave N and Thomas St in the Uptown Urban Center, situated between the residential Queen Anne neighborhood to the north, South Lake Union to the east, and Downtown to the south. Adjacent development includes a vacant lot to the north proposed as a future skate park, a commercial structure across the alley to the east proposed for redevelopment with an 8-story mixed use structure, a multifamily residential structure to the south, and a hotel to the west across 5th Ave N. The Seattle Center campus is located across Broad St to the northwest which includes a mix of the Seattle World's Fair landmark buildings, the Space Needle, Pacific Science Center and Museum of Pop Culture. Other development in the area include midrise residential structures, lowrise office buildings, and hotels in a variety of architectural styles.

5th Ave N is a principal arterial street. The elevated Seattle Monorail tracks run north, following the west side of 5th Ave N until Thomas St where they veer northwest into the Seattle Center. Thomas St is a designated Green Street and an important east/west connection linking the Cascade neighborhood and South Lake Union to the Seattle Center. An in-progress update to green street concept plan (Thomas Street Redefined) proposes a half block closure of Thomas Street adjacent to the project site and the development of a pedestrian plaza coordinated with the new skate park to create a grand entry to the Seattle Center.

Access:

Vehicular access is proposed from the alley to the west. Pedestrian access is proposed from 5th Ave N, Thomas St, and the alley.

Environmentally Critical Areas:

There are no mapped environmentally critical areas located on the subject site.

PROJECT DESCRIPTION

Design Review Early Design Guidance for an 8-story office building with restaurant and retail. Parking for 99 vehicles proposed. Existing building to be demolished.

The design packet includes information presented at the meeting, and is available online by entering the record number at this website:

<http://www.seattle.gov/DPD/aboutus/news/events/DesignReview/SearchPastReviews/default.aspx>

Any recording of the Board meeting is available in the project file. This meeting report summarizes the meeting and is not a meeting transcript.

The packet is also available to view in the file, by contacting the Public Resource Center at SDCI:

Mailing Public Resource Center
Address: 700 Fifth Ave., Suite 2000
P.O. Box 34019
Seattle, WA 98124-4019

Email: PRC@seattle.gov

EARLY DESIGN GUIDANCE February 5, 2020

PUBLIC COMMENT

The following public comments were offered at this meeting:

- Stated support for the project.
- Identified the prominence of the site and importance of 5th Ave N and Thomas St as a gateway to the Seattle Center.
- Recommended activation of the corner and embracing the pedestrian plaza proposed along Thomas St.
- Appreciated the fluidity of the corner in contrast to the sharp massing of the Hyatt across the street.
- Supported activation, retail and amenities along 5th Ave N.
- Supported maintaining the street trees.
- Supported respecting the new Thomas Street Redefined Concept Plan and taking advantage of the pedestrian plaza in coordination with SDOT.
- Concerned about activation of Thomas St. and recommended keeping the stairway and lobby open and orienting the ground level to support pedestrian activity.
- Recommended the incorporation of art, creative signage and lighting in support of the Uptown Arts and Culture District.
- Supported the bicycle parking locations.
- Supported preferred massing concept including the modulation, scale and form.
- Supported locating the primary entry on 5th Ave N.
- Supported the diversity and playfulness of the massing concept.

SDCI staff did not receive any design related comments in writing prior to the meeting.

The Seattle Department of Transportation offered the following comments:

- Supported taking all vehicle access and solid waste service from the alley.
- Noted there is no curbspace allocation along 5th Ave N for the project to utilize.
- Noted there is no curbspace allocation along Thomas St in the initial “Thomas St Redefined” concept design.
- Prioritized walking and biking along Thomas St.

One purpose of the design review process is for the Board and City to receive comments from the public that help to identify feedback and concerns about the site and design concept, identify applicable Seattle Design Guidelines and Neighborhood Design Guidelines of highest priority to the site and explore conceptual design, siting alternatives and eventual architectural design.

All public comments submitted in writing for this project can be viewed using the following link and entering the record number: <http://web6.seattle.gov/dpd/edms/>

PRIORITIES & BOARD RECOMMENDATIONS

After visiting the site, considering the analysis of the site and context provided by the proponents, and hearing public comment, the Design Review Board members provided the following siting and design guidance.

1. Massing Concept:

- a. While disappointed with the lack of development of the other two massing alternatives, the Board agreed that the applicant's preferred Option 3 was very compelling and strongly rooted in the context and unanimously recommended further development of this option. (CS2-1 Sense of Place, CS2-3 Corner Sites, DC2-5 Tall Buildings)
- b. The Board was supportive of the massing form reflecting the interior program, including the stacked amenities along Thomas St. (DC2-5 Tall Buildings)
- c. The Board's discussion on massing focused on the northeast corner and the relationship with the structure proposed across the alley. Due to the lack of massing views and information on the future development of this corner, the Board questioned how the sharp right angle related to the fluidity of the overall concept along Thomas St. and 5th Ave N. The Board did not prescribe specific recommendations for the corner treatment but requested a clear rationale articulating how the architectural concept wraps the full building including the northeast corner and the east facade. At the Recommendation meeting the Board expects to review views and perspectives all around the building to understand how it is experienced from all directions. The Board would also like to clearly understand the relationship with the proposal across the alley and any potential impacts. (CS2-1 Sense of Place, CS2-3 Corner Sites, DC2-5 Tall Buildings)

2. Ground Plane & Street Activation:

- a. The Board acknowledged the importance of the intersection of 5th Ave N and Thomas St. as a gateway to the Seattle Center, the planned development of Thomas St. as a pedestrian corridor through the Thomas Street Redefined Concept Plan, and the design efforts of the adjacent project to the west (#3028452-LU) to activate Thomas St.
- b. The Board also acknowledged public comment supporting activation of Thomas St. and coordination with the Thomas Street Redefined Concept Plan.
- c. The Board questioned whether the ground level program and vertical stair element with amenities would successfully activate Thomas St. and engage the public sphere.

Therefore, the Board requested thorough study of programming and design alternatives which legitimately activate the street frontage, enhance public life and support the Thomas Street Redefined Concept Plan as a pedestrian corridor. (PL1-1 Enhancing Open Spaces, PL2-2 Adding to Public Life, PL1-3 Pedestrian Volumes & Amenities, PL3-4 Retail Edges, DC1-A-1,2,&4 Arrangement of Interior Uses)

3. Materiality & Façade Articulation:

- a. The Board was generally supportive of the conceptual façade materiality indicated on pg. 47 of the packet including articulated glass cladding with depth, shadow, and additional materials. (CS2-1 Sense of Place, CS2-3 Corner Sites, DC2-5 Tall Buildings)
- b. The Board identified the importance of façade depth along the 5th Ave façade where there is less emphasis on modulation of the massing. (CS2-1 sense of Place, CS2-3 Corner Sites, DC2-5 Tall Buildings)
- c. The Board also provided guidance to articulate the alley façade and avoid a blank wall condition. (CS2-1 sense of Place, CS2-3 Corner Sites, DC2-5 Tall Buildings)
- d. The Board encouraged the development of a dynamic identity for the building in support of the underlying massing concept as well as the arts and culture nature of the neighborhood. (CS2-1 sense of Place, CS2-3 Corner Sites, DC2-5 Tall Buildings)

4. Bicycle Access: The Board acknowledged public comment regarding bicycle access and identified planning ahead for bicyclists as an important design consideration. A clear bicycle plan was requested which prioritizes safe access from Thomas St. (PL4-2-b Bike Connections)

5. Signage & Lighting: The Board encouraged the applicant to continue working with the public to develop creative signage and lighting which supports the Uptown Arts and Culture District. (CS2-1 sense of Place, CS2-3 Corner Sites)

6. Landscaping: While great importance has been placed on the Thomas St. frontage, the Board also identified the importance of landscaping along 5th Ave N to support retail activation and the pedestrian environment. (PL1-1 Enhancing Open Spaces, PL2-2 Adding to Public Life, PL1-3 Pedestrian Volumes & Amenities, PL3-4 Retail Edges)

DEVELOPMENT STANDARD DEPARTURES

The Board’s recommendation on the requested departure(s) will be based on the departure’s potential to help the project better meet these design guidelines priorities and achieve a better overall project design than could be achieved without the departure(s). The Board’s recommendation will be reserved until the final Board meeting.

At the time of the Early Design Guidance meeting no departures were requested.

DESIGN REVIEW GUIDELINES

The Seattle Design Guidelines and Neighborhood Design Guidelines recognized by the Board as Priority Guidelines are identified above. All guidelines remain applicable and are summarized below. For the full text please visit the [Design Review website](#).

CONTEXT & SITE

CS1 Natural Systems and Site Features: Use natural systems/features of the site and its surroundings as a starting point for project design.

CS1-A Energy Use

CS1-A-1. Energy Choices: At the earliest phase of project development, examine how energy choices may influence building form, siting, and orientation, and factor in the findings when making siting and design decisions.

CS1-B Sunlight and Natural Ventilation

CS1-B-1. Sun and Wind: Take advantage of solar exposure and natural ventilation. Use local wind patterns and solar gain to reduce the need for mechanical ventilation and heating where possible.

CS1-B-2. Daylight and Shading: Maximize daylight for interior and exterior spaces and minimize shading on adjacent sites through the placement and/or design of structures on site.

CS1-B-3. Managing Solar Gain: Manage direct sunlight falling on south and west facing facades through shading devices and existing or newly planted trees.

CS1-C Topography

CS1-C-1. Land Form: Use natural topography and desirable landforms to inform project design.

CS1-C-2. Elevation Changes: Use the existing site topography when locating structures and open spaces on the site.

CS1-D Plants and Habitat

CS1-D-1. On-Site Features: Incorporate on-site natural habitats and landscape elements into project design and connect those features to existing networks of open spaces and natural habitats wherever possible. Consider relocating significant trees and vegetation if retention is not feasible.

CS1-D-2. Off-Site Features: Provide opportunities through design to connect to off-site habitats such as riparian corridors or existing urban forest corridors. Promote continuous habitat, where possible, and increase interconnected corridors of urban forest and habitat where possible.

CS1-E Water

CS1-E-1. Natural Water Features: If the site includes any natural water features, consider ways to incorporate them into project design, where feasible

CS1-E-2. Adding Interest with Project Drainage: Use project drainage systems as opportunities to add interest to the site through water-related design elements.

Uptown Supplemental Guidance:

CS1-1 Topography

CS1-1-a. Street Grade: Step the elevation of ground floors so that building entrances and ground floors roughly match the street grade.

CS1-1-b. Step with the Grade: Design the building massing to step with grade using techniques such as changes in the levels of upper floors, breaks in the roofline, vertical and horizontal modulation, stepping facades.

CS1-1-c. Service & Access Impacts: Use existing grade changes to minimize service and access impacts in through-block developments.

CS1-1-d. Step Fencing: If fencing or screening is included in the design, it should step along with the topography.

CS1-1-e. Safe & Attractive Transition: Design ground-level treatments that create a safe, attractive transition between the building, site and the sidewalk such as terraces, stoops, rockeries, stairs, and landscaping, or other positive approaches used on adjacent properties. Create a transition between ground level interior and adjacent pedestrian areas and public sidewalks that achieves a balance of transparency for safety (eyes on the street) and screening for privacy.

CS1-2 Plants and Habitat

CS1-2-a. Habitat Landscapes: Create habitat landscapes of native species in building setbacks, right-of-ways, green roofs, walls and gardens. Look for opportunities to contribute to neighborhood and citywide connective habitats for insects and birds, while providing a safe environment for pedestrians.

CS2 Urban Pattern and Form: Strengthen the most desirable forms, characteristics, and patterns of the streets, block faces, and open spaces in the surrounding area.

CS2-A Location in the City and Neighborhood

CS2-A-1. Sense of Place: Emphasize attributes that give a distinctive sense of place. Design the building and open spaces to enhance areas where a strong identity already exists, and create a sense of place where the physical context is less established.

CS2-A-2. Architectural Presence: Evaluate the degree of visibility or architectural presence that is appropriate or desired given the context, and design accordingly.

CS2-B Adjacent Sites, Streets, and Open Spaces

CS2-B-1. Site Characteristics: Allow characteristics of sites to inform the design, especially where the street grid and topography create unusually shaped lots that can add distinction to the building massing.

CS2-B-2. Connection to the Street: Identify opportunities for the project to make a strong connection to the street and public realm.

CS2-B-3. Character of Open Space: Contribute to the character and proportion of surrounding open spaces.

CS2-C Relationship to the Block

CS2-C-1. Corner Sites: Corner sites can serve as gateways or focal points; both require careful detailing at the first three floors due to their high visibility from two or more streets and long distances.

CS2-C-2. Mid-Block Sites: Look to the uses and scales of adjacent buildings for clues about how to design a mid-block building. Continue a strong street-edge and respond to datum lines of adjacent buildings at the first three floors.

CS2-C-3. Full Block Sites: Break up long facades of full-block buildings to avoid a monolithic presence. Provide detail and human scale at street-level, and include repeating elements to add variety and rhythm to the façade and overall building design.

CS2-D Height, Bulk, and Scale

CS2-D-1. Existing Development and Zoning: Review the height, bulk, and scale of neighboring buildings as well as the scale of development anticipated by zoning for the area to determine an appropriate complement and/or transition.

CS2-D-2. Existing Site Features: Use changes in topography, site shape, and vegetation or structures to help make a successful fit with adjacent properties.

CS2-D-3. Zone Transitions: For projects located at the edge of different zones, provide an appropriate transition or complement to the adjacent zone(s). Projects should create a step in perceived height, bulk and scale between the anticipated development potential of the adjacent zone and the proposed development.

CS2-D-4. Massing Choices: Strive for a successful transition between zones where a project abuts a less intense zone.

CS2-D-5. Respect for Adjacent Sites: Respect adjacent properties with design and site planning to minimize disrupting the privacy of residents in adjacent buildings.

Uptown Supplemental Guidance:

CS2-1 Sense of Place

CS2-1-a. Identity Features: Use site identity features at Uptown Gateway locations. Examples of identity features include art, welcoming or wayfinding signage, distinct architecture or major public open space.

CS2-2 Adjacent Sites

CS2-2-a. Relationships & Connections: Buildings adjacent to the Seattle Center campus should be sited to create synergistic relationships and reinforce connections between the Seattle Center and the surrounding Uptown neighborhood.

CS2-3 Corner Sites

CS2-3-a. Address the Corner: Generally, buildings within Uptown should meet the corner and not be set back, except for Gateway locations. Buildings, retail treatments, and open spaces should address the corner and promote activity.

CS2-3-b. Corner Entrances: Generally, corner entrances are discouraged for retail uses. However, corner entrances may be appropriate to emphasize Gateways or locations with high pedestrian activity within the Heart of Uptown.

CS2-3-c. Special Features: Corner sites are often desirable locations for small publicly-accessible plazas, art, and other special features.

CS3 Architectural Context and Character: Contribute to the architectural character of the neighborhood.

CS3-A Emphasizing Positive Neighborhood Attributes

CS3-A-1. Fitting Old and New Together: Create compatibility between new projects, and existing architectural context, including historic and modern designs, through building articulation, scale and proportion, roof forms, detailing, fenestration, and/or the use of complementary materials.

CS3-A-2. Contemporary Design: Explore how contemporary designs can contribute to the development of attractive new forms and architectural styles; as expressed through use of new materials or other means.

CS3-A-3. Established Neighborhoods: In existing neighborhoods with a well-defined architectural character, site and design new structures to complement or be compatible with the architectural style and siting patterns of neighborhood buildings.

CS3-A-4. Evolving Neighborhoods: In neighborhoods where architectural character is evolving or otherwise in transition, explore ways for new development to establish a positive and desirable context for others to build upon in the future.

CS3-B Local History and Culture

CS3-B-1. Placemaking: Explore the history of the site and neighborhood as a potential placemaking opportunity. Look for historical and cultural significance, using neighborhood groups and archives as resources.

CS3-B-2. Historical/Cultural References: Reuse existing structures on the site where feasible as a means of incorporating historical or cultural elements into the new project.

Uptown Supplemental Guidance:

CS3-1 Placemaking

CS3-1-a. Design Features: Include design features that make the Arts and Cultural District visible to pedestrians such as interpretive panels, banners, plaques, building names, wayfinding, signage and art.

CS3-1-b. Visual Art: Make visual art an integral part of the design concept, especially along Mercer/Roy Street corridor, near theaters and other cultural venues, and in the Heart of Uptown.

PUBLIC LIFE

PL1 Connectivity: Complement and contribute to the network of open spaces around the site and the connections among them.

PL1-A Network of Open Spaces

PL1-A-1. Enhancing Open Space: Design the building and open spaces to positively contribute to a broader network of open spaces throughout the neighborhood.

PL1-A-2. Adding to Public Life: Seek opportunities to foster human interaction through an increase in the size and quality of project-related open space available for public life.

PL1-B Walkways and Connections

PL1-B-1. Pedestrian Infrastructure: Connect on-site pedestrian walkways with existing public and private pedestrian infrastructure, thereby supporting pedestrian connections within and outside the project.

PL1-B-2. Pedestrian Volumes: Provide ample space for pedestrian flow and circulation, particularly in areas where there is already heavy pedestrian traffic or where the project is expected to add or attract pedestrians to the area.

PL1-B-3. Pedestrian Amenities: Opportunities for creating lively, pedestrian oriented open spaces to enliven the area and attract interest and interaction with the site and building should be considered.

PL1-C Outdoor Uses and Activities

PL1-C-1. Selecting Activity Areas: Concentrate activity areas in places with sunny exposure, views across spaces, and in direct line with pedestrian routes.

PL1-C-2. Informal Community Uses: In addition to places for walking and sitting, consider including space for informal community use such as performances, farmer’s markets, kiosks and community bulletin boards, cafes, or street vending.

PL1-C-3. Year-Round Activity: Where possible, include features in open spaces for activities beyond daylight hours and throughout the seasons of the year, especially in neighborhood centers where active open space will contribute vibrancy, economic health, and public safety.

Uptown Supplemental Guidance:

PL1-1 Enhancing Open Spaces

PL1-1-a. Connections: Locate plazas intended for public use at or near grade to promote both a physical and visual connection to the street. Where publicly accessible plazas abut private open space, use special paving materials, landscaping, and other elements to provide a clear definition between the public and private realms.

PL1-2 Adding to Public Life

PL1-2-a. Adjacency to Seattle Center: Opportunities to add to public life are especially important for street-facing facades that are adjacent to the Seattle Center.

PL1-3 Pedestrian Volumes and Amenities

PL1-3-a. Volume & Flow: Encourage streetscapes that respond to unique conditions created by Seattle Center. Design wide sidewalks, sturdy street furniture and durable landscaping to accommodate high pedestrian volumes and flow of event crowds.

PL1-3-b. Notable Locations: Pedestrian amenities are especially encouraged in the Heart of Uptown, and along the Queen Anne Ave. and 1st Ave N corridors.

PL1-3-c. Pedestrian Uses: All of Uptown should be considered a “walking district.” New development should strive to support outdoor uses, activities and seating that create an attractive and vibrant pedestrian environment. Consider widening narrow sidewalks though additional building setback at street level.

PL1-4 Outdoor Uses and Activities

PL1-4-a. Outdoor Dining: Encourage outdoor dining throughout Uptown.

PL2 Walkability: Create a safe and comfortable walking environment that is easy to navigate and well-connected to existing pedestrian walkways and features.

PL2-A Accessibility

PL2-A-1. Access for All: Provide access for people of all abilities in a manner that is fully integrated into the project design. Design entries and other primary access points such that all visitors can be greeted and welcomed through the front door.

PL2-A-2. Access Challenges: Add features to assist pedestrians in navigating sloped sites, long blocks, or other challenges.

PL2-B Safety and Security

PL2-B-1. Eyes on the Street: Create a safe environment by providing lines of sight and encouraging natural surveillance.

PL2-B-2. Lighting for Safety: Provide lighting at sufficient lumen intensities and scales, including pathway illumination, pedestrian and entry lighting, and/or security lights.

PL2-B-3. Street-Level Transparency: Ensure transparency of street-level uses (for uses such as nonresidential uses or residential lobbies), where appropriate, by keeping views open into spaces behind walls or plantings, at corners, or along narrow passageways.

PL2-C Weather Protection

PL2-C-1. Locations and Coverage: Overhead weather protection is encouraged and should be located at or near uses that generate pedestrian activity such as entries, retail uses, and transit stops.

PL2-C-2. Design Integration: Integrate weather protection, gutters and downspouts into the design of the structure as a whole, and ensure that it also relates well to neighboring buildings in design, coverage, or other features.

PL2-C-3. People-Friendly Spaces: Create an artful and people-friendly space beneath building.

PL2-D Wayfinding

PL2-D-1. Design as Wayfinding: Use design features as a means of wayfinding wherever possible.

PL3 Street-Level Interaction: Encourage human interaction and activity at the street-level with clear connections to building entries and edges.

PL3-A Entries

PL3-A-1. Design Objectives: Design primary entries to be obvious, identifiable, and distinctive with clear lines of sight and lobbies visually connected to the street.

PL3-A-2. Common Entries: Multi-story residential buildings need to provide privacy and security for residents but also be welcoming and identifiable to visitors.

PL3-A-3. Individual Entries: Ground-related housing should be scaled and detailed appropriately to provide for a more intimate type of entry.

PL3-A-4. Ensemble of Elements: Design the entry as a collection of coordinated elements including the door(s), overhead features, ground surface, landscaping, lighting, and other features.

PL3-B Residential Edges

PL3-B-1. Security and Privacy: Provide security and privacy for residential buildings through the use of a buffer or semi-private space between the development and the street or neighboring buildings.

PL3-B-2. Ground-level Residential: Privacy and security issues are particularly important in buildings with ground-level housing, both at entries and where windows are located overlooking the street.

PL3-B-3. Buildings with Live/Work Uses: Maintain active and transparent facades in the design of live/work residences. Design the first floor so it can be adapted to other commercial use as needed in the future.

PL3-B-4. Interaction: Provide opportunities for interaction among residents and neighbors.

PL3-C Retail Edges

PL3-C-1. Porous Edge: Engage passersby with opportunities to interact visually with the building interior using glazing and transparency. Create multiple entries where possible and make a physical and visual connection between people on the sidewalk and retail activities in the building.

PL3-C-2. Visibility: Maximize visibility into the building interior and merchandise displays. Consider fully operational glazed wall-sized doors that can be completely opened to the street, increased height in lobbies, and/or special lighting for displays.

PL3-C-3. Ancillary Activities: Allow space for activities such as sidewalk vending, seating, and restaurant dining to occur. Consider setting structures back from the street or incorporating space in the project design into which retail uses can extend.

Uptown Supplemental Guidance:

PL3-1 Entries

PL3-1-a. Pedestrian Orientation: Design entries to be pedestrian-friendly. Consider how the position, scale, architectural detailing, and materials will create an entry that is clearly discernible to the pedestrian.

PL3-1-b. Safety Sightlines & Features: Individual or unit entrances in buildings that are accessed from the sidewalk or other public spaces should consider safety sightlines as well as safety features such as decorative fencing and high visibility gating. Landscaping should be consistent with these features.

PL3-1-c. Design Features: The use of distinctive paving, detailing, materials and landscaping, and artistic designs with cultural references is strongly encouraged. Building addresses and names (if applicable) should be located at entrances, and tastefully crafted.

PL3-2 Residential Edges on Pedestrian Streets

PL3-2-a. Security: Where residential buildings are located along the pedestrian-oriented Class 1 or Class 2 Pedestrian Streets, include façade lighting and visible lobbies or public-facing retail spaces to enhance the security of the adjacent sidewalk.

PL3-3 Ground Level Residential Edges (Including Live/Work Uses)

PL3-3-a. Entries: Provide a direct entry into the unit from the street. The entry should include weather protection sufficient to shelter persons entering the building during inclement weather.

PL3-3-b. Elevate the Ground Floor: Elevating the ground floor of the living area two to four feet above the adjacent sidewalk grade to increase privacy is desirable. This design guideline does not apply to designated ADA accessible units.

PL3-3-c. Boundaries: Provide a physical “threshold” feature such as a hedge, retaining wall, rockery, stair, railing, or a combination of such elements on private property that defines and bridges the boundary between public right-of-way and private yard or patio. Thresholds may screen but not block views to and from the street and should help define individual units. Retaining walls should generally not be taller than four feet. If additional height is required to accommodate grade conditions, then terraces can be employed.

PL3-3-d. Gates & Fencing: Where gates and fencing are used as threshold features, design them for high visibility and incorporate landscaping to soften these features.

PL3-4 Retail Edges

PL3-4-a. Retail Size: Smaller store-front shops are preferred along Class 1 and Class 2 Pedestrian Streets to accommodate smaller local retailers and provide affordable retail space options.

PL4 Active Transportation: Incorporate design features that facilitate active forms of transportation such as walking, bicycling, and use of transit.

PL4-A Entry Locations and Relationships

PL4-A-1. Serving all Modes of Travel: Provide safe and convenient access points for all modes of travel.

PL4-A-2. Connections to All Modes: Site the primary entry in a location that logically relates to building uses and clearly connects all major points of access.

PL4-B Planning Ahead for Bicyclists

PL4-B-1. Early Planning: Consider existing and future bicycle traffic to and through the site early in the process so that access and connections are integrated into the project along with other modes of travel.

PL4-B-2. Bike Facilities: Facilities such as bike racks and storage, bike share stations, shower facilities and lockers for bicyclists should be located to maximize convenience, security, and safety.

PL4-B-3. Bike Connections: Facilitate connections to bicycle trails and infrastructure around and beyond the project.

PL4-C Planning Ahead For Transit

PL4-C-1. Influence on Project Design: Identify how a transit stop (planned or built) adjacent to or near the site may influence project design, provide opportunities for placemaking.

PL4-C-2. On-site Transit Stops: If a transit stop is located onsite, design project-related pedestrian improvements and amenities so that they complement any amenities provided for transit riders.

PL4-C-3. Transit Connections: Where no transit stops are on or adjacent to the site, identify where the nearest transit stops and pedestrian routes are and include design features and connections within the project design as appropriate.

Uptown Supplemental Guidance:

PL4-1 Entry Locations and Relationships

PL4-1-a. Consider Transit Riders: When buildings are located adjacent to a major transit stop, integrate weather protection and public seating for bus riders into the design of the building to eliminate the need for a bus shelter, and enhance the function and safety of the pedestrian environment.

PL4-2 Planning Ahead for Bicyclists

PL4-2-a. Bike Facilities: Placement of long-term bicycle storage should consider cyclist safety and ease of access. Provide the required short-term bike racks near main building entrance to accommodate private and shared bicycles. Consider customizing the SDOT approved racks (“inverted U” or “staple” style) to reflect Uptown Arts and Cultural District branding such as colors, distinctive place-names, plaques, or other design elements.

PL4-2-b. Bike Connections: Facilitate connections to major bicycle infrastructure including the Thomas Street Bridge/Elliot Bay Trail, Mercer Street protected bike lane and 2nd Avenue/Denny Way protected bike lane.

PL4-3 Transit Facilities

PL4-3-a. Pedestrian Activity: Transit facilities should be designed as an integral part of any co-development and be designed to support all relevant Citywide Design Guidelines, especially those regarding the ground floor and pedestrian activity.

1. On Class I Pedestrian Streets, required street level uses are essential to achieving the intent of Pedestrian Street Classifications. Operational needs may require that vehicle entrances to transit facilities be wider than permitted for parking garages, and facade lengths may be greater than other structures in the neighborhood. Street frontage of these projects should maintain and reinforce the levels of pedestrian activity and visual interest that Class I Pedestrian streets are intended to achieve.
2. On all streets bus layover facilities should completely screen the layover space from public view. Ideally other uses with transparent, active storefronts are located between bus parking and all adjacent, street public right of way.

DESIGN CONCEPT

DC1 Project Uses and Activities: Optimize the arrangement of uses and activities on site.

DC1-A Arrangement of Interior Uses

DC1-A-1. Visibility: Locate uses and services frequently used by the public in visible or prominent areas, such as at entries or along the street front.

DC1-A-2. Gathering Places: Maximize the use of any interior or exterior gathering spaces.

DC1-A-3. Flexibility: Build in flexibility so the building can adapt over time to evolving needs, such as the ability to change residential space to commercial space as needed.

DC1-A-4. Views and Connections: Locate interior uses and activities to take advantage of views and physical connections to exterior spaces and uses.

DC1-B Vehicular Access and Circulation

DC1-B-1. Access Location and Design: Choose locations for vehicular access, service uses, and delivery areas that minimize conflict between vehicles and non-motorists wherever possible. Emphasize use of the sidewalk for pedestrians, and create safe and attractive conditions for pedestrians, bicyclists, and drivers.

DC1-B-2. Facilities for Alternative Transportation: Locate facilities for alternative transportation in prominent locations that are convenient and readily accessible to expected users.

DC1-C Parking and Service Uses

DC1-C-1. Below-Grade Parking: Locate parking below grade wherever possible. Where a surface parking lot is the only alternative, locate the parking in rear or side yards, or on lower or less visible portions of the site.

DC1-C-2. Visual Impacts: Reduce the visual impacts of parking lots, parking structures, entrances, and related signs and equipment as much as possible.

DC1-C-3. Multiple Uses: Design parking areas to serve multiple uses such as children's play space, outdoor gathering areas, sports courts, woonerf, or common space in multifamily projects.

DC1-C-4. Service Uses: Locate and design service entries, loading docks, and trash receptacles away from pedestrian areas or to a less visible portion of the site to reduce possible impacts of these facilities on building aesthetics and pedestrian circulation.

DC2 Architectural Concept: Develop an architectural concept that will result in a unified and functional design that fits well on the site and within its surroundings.

DC2-A Massing

DC2-A-1. Site Characteristics and Uses: Arrange the mass of the building taking into consideration the characteristics of the site and the proposed uses of the building and its open space.

DC2-A-2. Reducing Perceived Mass: Use secondary architectural elements to reduce the perceived mass of larger projects.

DC2-B Architectural and Facade Composition

DC2-B-1. Façade Composition: Design all building facades—including alleys and visible roofs— considering the composition and architectural expression of the building as a whole. Ensure that all facades are attractive and well-proportioned.

DC2-B-2. Blank Walls: Avoid large blank walls along visible façades wherever possible. Where expanses of blank walls, retaining walls, or garage facades are unavoidable, include uses or design treatments at the street level that have human scale and are designed for pedestrians.

DC2-C Secondary Architectural Features

DC2-C-1. Visual Depth and Interest: Add depth to facades where appropriate by incorporating balconies, canopies, awnings, decks, or other secondary elements into the façade design. Add detailing at the street level in order to create interest for the pedestrian and encourage active street life and window shopping (in retail areas).

DC2-C-2. Dual Purpose Elements: Consider architectural features that can be dual purpose— adding depth, texture, and scale as well as serving other project functions.

DC2-C-3. Fit With Neighboring Buildings: Use design elements to achieve a successful fit between a building and its neighbors.

DC2-D Scale and Texture

DC2-D-1. Human Scale: Incorporate architectural features, elements, and details that are of human scale into the building facades, entries, retaining walls, courtyards, and exterior spaces in a manner that is consistent with the overall architectural concept

DC2-D-2. Texture: Design the character of the building, as expressed in the form, scale, and materials, to strive for a fine-grained scale, or “texture,” particularly at the street level and other areas where pedestrians predominate.

DC2-E Form and Function

DC2-E-1. Legibility and Flexibility: Strive for a balance between building use legibility and flexibility. Design buildings such that their primary functions and uses can be readily determined from the exterior, making the building easy to access and understand. At the same time, design flexibility into the building so that it may remain useful over time even as specific programmatic needs evolve.

Uptown Supplemental Guidance:

DC2-1 Architectural Context

DC2-1-a. Arts & Cultural District: Architecture that emphasizes human scale, streetscape rhythm, quality detailing and materials is more important than consistency with a particular period or style. Uptown’s evolving and dynamic architectural context embraces a range of historical styles, and modern innovative design that reflects the Uptown Arts and Cultural District.

DC2-2 Blank Walls and Retaining Walls

DC2-2-a. Artwork & Murals: Artwork and murals, created in collaboration with the Uptown Arts and Cultural Coalition, are encouraged for any temporary or permanent blank walls.

DC2-2-b. Pattern & Texture: Throughout Uptown any visible retaining walls should be constructed of materials that will provide substantial pattern and texture. Rockery, stone, stacked stone or stained concrete, or brick are preferred. Walls should be appropriately designed and scaled for the pedestrian environment. Landscaping or art in conjunction with retaining walls is strongly encouraged.

DC2-3 Secondary Architectural Features

DC2-3-a. Storefront Design: Design storefronts to allow and encourage tenants to create individualized architectural features.

DC2-3-b. Window Design: Encourage substantial window detailing and recessed windows. Discourage flush window treatments.

DC2-4 Dual Purpose Elements

DC2-4-a. Canopies & Weather Protection: The use of exterior canopies or other weather protection features is favored throughout Uptown for residential and commercial uses. Canopies and awnings should be sized to the scale of the building and the pedestrian, and blend well with the building and surroundings.

DC2-5 Tall Buildings

DC2-5-a. Response to Context: Integrate and transition to a surrounding fabric of differing heights; relate to existing visual datums, the street wall and parcel patterns. Respond to prominent nearby sites and/or sites with axial focus or distant visibility, such as waterfronts, public view corridors, street ends.

DC2-5-b. Tall Form Placement, Spacing & Orientation: Locate the tall forms to optimize the following: minimize shadow impacts on public parks, plazas and places; maximize tower spacing to adjacent structures; afford light and air to the streets, pedestrians and public realm; and minimize general impacts to nearby existing and future planned occupants.

DC2-5-c. Tall Form Design: Avoid long slabs and big, unmodulated boxy forms, which cast bigger shadows and lack scale or visual interest. Consider curved, angled, shifting and/or carved yet coherent forms. Shape and orient tall floorplates based on context, nearby opportunities and design concepts, not simply to maximize internal efficiencies. Modulation should be up-sized to match the longer, taller view distances.

DC2-5-d. Intermediate Scales: To mediate the extra height/scale, add legible, multi-story intermediate scale elements: floor groupings, gaskets, off-sets, projections, sky terraces, layering, or other legible modulations to the middle of tall forms. Avoid a single repeated extrusion from base to top.

DC2-5-e. Shape & Design All Sides: Because tall forms are visible from many viewpoints/distances, intentionally shape the form and design of all sides (even party walls), responding to differing site patterns and context relationships. Accordingly, not all sides may have the same forms or display identical cladding.

DC2-5-f. Adjusted Base Scale: To mediate the form's added height, design a 1-3 story base scale, and/or highly legible base demarcation to transition to the ground and mark

the 'street room' proportion. Tall buildings require several scale readings, and the otherwise typical single-story ground floor appears squashed by the added mass above.

DC2-5-g. Ground Floor Uses: Include identifiable primary entrances -scaled to the tall form - and provide multiple entries. Include genuinely activating uses or grade-related residences to activate all streets.

DC2-5-h. Facade Depth & Articulation: Use plane changes, depth, shadow, and texture to provide human scale and interest and to break up the larger façade areas of tall buildings, especially in the base and lower 100 feet. Compose fenestration and material dimensions to be legible and richly detailed from long distances.

DC2-5-i. Quality & 6th Elevations: Intentionally design and employ quality materials and detailing, including on all soffits, balconies, exterior ceilings and other surfaces seen from below, including lighting, vents, etc.

DC2-5-j. Transition to the Sky & Skyline Composition: Create an intentional, designed terminus to the tall form and enhance the skyline (not a simple flat 'cut-off'). Integrate all rooftop elements and uses into the overall design, including mechanical screens, maintenance equipment, amenity spaces and lighting. Use wide photo simulations to study & design how the tall building will contribute to the overall skyline profile and variety of forms.

DC3 Open Space Concept: Integrate open space design with the building design so that they complement each other.

DC3-A Building-Open Space Relationship

DC3-A-1. Interior/Exterior Fit: Develop an open space concept in conjunction with the architectural concept to ensure that interior and exterior spaces relate well to each other and support the functions of the development.

DC3-B Open Space Uses and Activities

DC3-B-1. Meeting User Needs: Plan the size, uses, activities, and features of each open space to meet the needs of expected users, ensuring each space has a purpose and function.

DC3-B-2. Matching Uses to Conditions: Respond to changing environmental conditions such as seasonal and daily light and weather shifts through open space design and/or programming of open space activities.

DC3-B-3. Connections to Other Open Space: Site and design project-related open spaces to connect with, or enhance, the uses and activities of other nearby public open space where appropriate.

DC3-B-4. Multifamily Open Space: Design common and private open spaces in multifamily projects for use by all residents to encourage physical activity and social interaction.

DC3-C Design

DC3-C-1. Reinforce Existing Open Space: Where a strong open space concept exists in the neighborhood, reinforce existing character and patterns of street tree planting, buffers or treatment of topographic changes. Where no strong patterns exist, initiate a strong open space concept that other projects can build upon in the future.

DC3-C-2. Amenities/Features: Create attractive outdoor spaces suited to the uses envisioned for the project.

DC3-C-3. Support Natural Areas: Create an open space design that retains and enhances onsite natural areas and connects to natural areas that may exist off-site and may provide habitat for wildlife.

DC4 Exterior Elements and Finishes: Use appropriate and high quality elements and finishes for the building and its open spaces.

DC4-A Exterior Elements and Finishes

DC4-A-1. Exterior Finish Materials: Building exteriors should be constructed of durable and maintainable materials that are attractive even when viewed up close. Materials that have texture, pattern, or lend themselves to a high quality of detailing are encouraged.

DC4-A-2. Climate Appropriateness: Select durable and attractive materials that will age well in Seattle’s climate, taking special care to detail corners, edges, and transitions.

DC4-B Signage

DC4-B-1. Scale and Character: Add interest to the streetscape with exterior signs and attachments that are appropriate in scale and character to the project and its environs.

DC4-B-2. Coordination with Project Design: Develop a signage plan within the context of architectural and open space concepts, and coordinate the details with façade design, lighting, and other project features to complement the project as a whole, in addition to the surrounding context.

DC4-C Lighting

DC4-C-1. Functions: Use lighting both to increase site safety in all locations used by pedestrians and to highlight architectural or landscape details and features such as entries, signs, canopies, plantings, and art.

DC4-C-2. Avoiding Glare: Design project lighting based upon the uses on and off site, taking care to provide illumination to serve building needs while avoiding off-site night glare and light pollution.

DC4-D Trees, Landscape, and Hardscape Materials

DC4-D-1. Choice of Plant Materials: Reinforce the overall architectural and open space design concepts through the selection of landscape materials.

DC4-D-2. Hardscape Materials: Use exterior courtyards, plazas, and other hard surfaced areas as an opportunity to add color, texture, and/or pattern and enliven public areas through the use of distinctive and durable paving materials. Use permeable materials wherever possible.

DC4-D-3. Long Range Planning: Select plants that upon maturity will be of appropriate size, scale, and shape to contribute to the site as intended.

DC4-D-4. Place Making: Create a landscape design that helps define spaces with significant elements such as trees.

DC4-E Project Assembly and Lifespan

DC4-E-1. Deconstruction: When possible, design the project so that it may be deconstructed at the end of its useful lifetime, with connections and assembly techniques that will allow reuse of materials.

Uptown Supplemental Guidance:

DC4-1 Building Materials

DC4-1-a. Exterior Treatments: Decorative exterior treatments using brick, tile, and/or other interesting more modern exterior finish materials are strongly preferred.

DC4-1-b. Quality Materials: Quality exterior finish materials should be incorporated at all levels and on all exterior walls. Materials at the street level should be of the highest quality.

DC4-1-c. Compatible Materials: Use materials, colors, and details to unify a building's appearance; buildings and structures should be clad with compatible materials on all sides. Where buildings have side setbacks adjacent to other buildings, materials and design treatments should intentionally 'wrap the corner' of window and door openings, and at building corners, so cladding materials and treatments appear substantial, and not two-dimensional or paper thin.

DC4-1-d. Stucco: The use of stucco is strongly discouraged.

DC4-2 Commercial Signage

DC4-2-a. Pedestrian-Scale Signage: Pedestrian-scale commercial signage such as blade signs, wall-mounted signs, and signs below awnings, are encouraged. Signs for arts and cultural uses that incorporate elements of color and light are also encouraged.

DC4-2-b. Creative Expression: Storefront signs that integrate creativity and individual expression into the overall design of storefronts are encouraged. Signs that appear cluttered and detract from the quality of the building's design are discouraged.

DC4-3 Commercial Lighting

DC4-3-a. Pedestrian-Scale Lighting: Uptown accommodates shopping and eating experiences during the dark hours of the Northwest's late fall, winter, and early spring. Pedestrian-scale lighting for both the public sidewalks and private pathways is encouraged.

DC4-3-b. Visual Interest: Creative distinct lighting fixtures and schemes that enhance the unique identity of the Uptown Arts and Cultural District is strongly encouraged. Lighting should add visual interest for both pedestrians and drivers while not disturbing any adjacent residential properties.

DC4-4 Trees, Landscape and Hardscape Materials

DC4-4-a. Hardscape Design: Consider the use of permeable pavement or artistic design elements where landscaped design elements are not feasible or sustainable.

BOARD DIRECTION

At the conclusion of the Early Design Guidance meeting, the Board recommended moving forward to MUP application.