


DEADBREAK STRAIGHT LINE CONNECTOR 600 AMP, 13 KV and 26 KV



Standards Coordinator
Robin Byun

Standards Supervisor
John Shipek

Unit Director
Darnell Cola

Robin Byun

John Shipek

Darnell Cola

**DEADBREAK STRAIGHT LINE CONNECTOR
 600 AMP, 13 KV & 26 KV**

MATERIAL LIST

ITEM	QTY	DESCRIPTION	STOCK NO.
1	3	STRAIGHT RECEPTACLE, including housing, connector, adapter and bolts	687437
2	3	LUG, compression	#1 686375 1/0 686377 2/0 686376 3/0 686378
3	3	RING, retaining	#1 687604 #2 to 3/0 687606
4	3	ADAPTER, cable	#1 - 15 kV 686310 #1 - 28 kV 686370 2/0 - 15 kV 686315 3/0 - 15 kV 686315
5	3	GROUNDING ADAPTER KIT	350 to 1000 kcmil 686512
	3	CONSTANT FORCE SPRING for #2 to 500 kcmil, included	686514
6	20'	BRAID, Copper	618624
7	1	TERMINAL, compression, 1/2", #2 Copper for Copper bus	677071E
8	1	BOLT, 1/2" x 1-1/2", Si Bronze	784587E
9	1	NUT, 1/2", Si Bronze	783325E
10	1	WASHER, flat, 1/2", Bronze	788026E
11	1	WASHER, split lock, 1/2", Bronze	788125E
12	6'	WIRE, #2, Bare Stranded Copper	610434
13	1	CONNECTOR, "C", #2 to #2	677326E

NOTES:

- Lubricate parts slightly with silicon grease provided in kit. **No substitutions.**
- Torque brass bolt for adapter to 60 foot-pounds.
- Torque compression lug to between 50 to 60 foot-pounds.
- Connect Item 5 permanently to other drain wires and then to transformer neutral spade connector for star primary transformers.