

## **Seattle Fire Prevention Division**

220 3rd Avenue South Seattle, WA 98104 SFD\_FMO\_SystemsTesting@seattle.gov

## **SYSTEM TEST REPORT**

HOOD SUPPRESSION		STATUS					
Confidence Test	☐ Deficiency Repair Test	Red	☐ Yellow	☐ White			
Occupancy Information							
Premises Name: Premises Address:							
Contact Name:		Contact Phone:					
Contact Address:		Contact Email:					
Central Station Monitoring	: Yes No 1/A	Monitoring Require	d: [	Yes No			
Monitoring Company Name	e:	Monitoring Compan	ny Phone:				
<b>Hood Inventory - Multiple</b>	Systems in a Building May Be Rep	orted on a Single Fo	rm (M-mandatory)				
Hood Suppression System I	D (one per system) (M):						
Make:							
Model:							
Is system UL300 capable?	☐ Yes ☐	No					
Size (gal):							
Style:							
Location of Cylinder(s):							
Last Hydro-test Date (mont	:h/year):						
System coverage/location (	(deli, main line, bakery station) (M)	:					
List covered cooking appliances from left to right (M):							
Upload photo or sketch of	suppression system and protected	appliances:	Yes	No			
Inspection & Testing Agen							
Company Name:		Phone:					
Address:		Emergency Phone:					
		Email:					
Inspector/Tester Informat	ion						
Inspector Name:							
Certification No.:							
Test Information							
Date of Test:							
The items on the checklists	below shall be inspected and teste	ed. This list may not	constitute all of the	required inspecting and			
testing of the fire and life s	afety system. Refer to the Fire Cod	e used by the AHJ, N	FPA 17, NFPA 17A, a	and NFPA 96 and			
manufacturer's recommendations for inspecting and testing requirements.							
PRE-TEST CHECKS							
AVOID "FALSE ALARMS" TO FIRE DEPARTMENT BY PUTTING THE FIRE ALARM SYSTEM IN TEST MODE. Failure to place the Fire							
Alarm System (FAS) into test mode and/or taking other precautions to may cause preventable alarms.							
1 The suppression syster	1 The suppression system meets the UL300 standard.						
Select "No" if the system is non-UL300 and any of the following three statements is true (if any of the following is true for							
a non-UL300 system, it must be replaced and until replacement, this is a deficiency):							
<ul> <li>Vegetable oil is the medium used by the cooking appliance.</li> </ul>							
<ul> <li>Parts are no longer a</li> </ul>	<ul> <li>Parts are no longer available for repair/maintenance of the current system.</li> </ul>						
<ul> <li>Coverage provided b</li> </ul>	y the system is not adequate for th	e protected applian	ce.				

APF	LIANCE COVERAGE, NOZZLES, AND PIPING			
2	All cooking appliances that can produce grease laden vapors are completely	☐ Yes	☐ No	
	under the range hood.	☐ 1es		
3	All cooking appliances have the required number and type of nozzles to	☐ Yes	☐ No	
	provide adequate fire protection.	res		
4	All nozzles are properly positioned.	☐ Yes	☐ No	
5	All piping and conduit are immobilized with proper hangers and brackets.	Yes Yes	☐ No	
6	List covered cooking appliances as currently			
	installed under hood from left to right:			
7	Are locations of covered appliances consistent with image stored in TCE			
	showing appliance locations? If not, upload accurate picture or sketch.	☐ Yes	☐ No	□ N/A
	Answer "yes" once accurate image is uploaded.	_	_	
8	For systems installed in 2018, or later, there is a placard that depicts			
	the type and location of appliance protected underneath the range hood of			
	the fire protection system, and the appliances being protected are	☐ Yes	☐ No	□ N/A
	consistent with the depiction in the placard. (Only use N/A for systems			L 13//
	installed prior to 2018.)			
SYS	TEM CONTROLS			
9	All system controls and components are accessible and free from			
	obstructions.	Yes Yes	☐ No	
10	The system is operational from the terminal link (last fusible link).	☐ Yes	☐ No	
11	The fusible links were replaced. (At 6 month intervals)	Yes	No	
12	The manual (remote) pull is configured correctly and is operational.	Yes	No	
13	The operation of the fusible link line is not impaired by grease.	 ☐ Yes	No	
14	The micro switch that controls the gas and/or electrical power to the			
	appliances functions properly.	Yes	☐ No	
15	The gas shuts down upon system activation.	☐ Yes	☐ No	□ N/A
	All sources of cooking heat shut down properly. Make up air shuts down if	Yes	☐ No	□ N/A
	present.	_	_	
CYL	INDERS AND EXTINGUISHING AGENT			
17	The extinguishing agent in the cylinders conforms to the manufacturer's	□Vos	ПМо	
	requirements for this system.	∐ Yes	∐ No	
18	The system has adequate supply of extinguishing agent as required to meet	□ Vos	□ No	
	the demand for complete coverage of the cooking appliances.	Yes Yes	☐ No	
19	The cylinders are filled with the correct volume of extinguishing agent.	☐ Yes	☐ No	
20	If present, the cylinder gauge is in the operational range.	Yes	☐ No	☐ N/A
21	If present, the CO2 or nitrogen Nitrogen cylinder is fully charged. (According	□ Voc	□ No	□ N/A
	to weight)	☐ Yes	☐ No	□ N/A
22	The hydrostatic testing of the agent cylinder(s) is up-to-date.	Yes	☐ No	
SYS	TEM SECURITY AND MONITORING			
23	The tamper seals on the suppression system were replaced.	☐ Yes	☐ No	
24	The suppression system is connected to the fire alarm panel. (Only select	☐ Yes	☐ No	□ N/A
	N/A if there is no fire alarm system)	1C3		L 11/7
25	The fire alarm panel receives the proper signals upon suppression system	☐ Yes	☐ No	□ N/A
	activation.	☐ 1E3		L 13/A
26	The alarm monitoring company received the alarm signal. (Only select N/A if	☐ Yes	☐ No	□ N/A
	there is no fire alarm system.)			L 11/A

INSPECTION FOR GREASE BUILDUP AND CLEANING						
27 The commercial cooking fire sup appears:	pression hood and exhaust system	☐ Clean	□ Dirty - Cleaning re	ecommended		
28 Advised personnel on the import clean?	ance of keeping hood, ducts, and file	ters Yes	☐ No			
FINAL CHECKS, TAGGING, AND REPO	RTS					
Put the Fire Alarm/monitoring system back into service and/or other precautionary measures that were made to restore fire alarm system to normal operation (includes removal of protective coverings.)						
	(deficient) or white (normal operation and the manual pull handle indication) inspection today.	· -	□No			
The color of the tag is:		☐ Red	☐ Yellow	☐ White		
30 I will provide a copy of the confic	lence test report to the owner.	☐ Yes	☐ No			
31 I will submit this test report to th	e fire department through TCE.	☐ Yes	☐ No			
By accepting this statement I, the certified technician shown on this form, certify that this fire protection system(s) has been properly inspected for functional operation in accordance with the current Fire Code (FC) used by the department that has jurisdiction and NFPA Standards adopted by the FC for this system. Any deficiencies found are noted in the report and have been reported to the building Owner/Manager for corrective action.						
I I I I I I I I I I I I I I I I I I I	orized to submit this report for the convey who has accepted this statement.	ertified	(Initials of Emp	oloyee)		
SIGNATURE (OPTIONAL)						
Signature of Technician						
Signature of Building Representative						

## **System Testing Reports Must Be Submitted Online**

Submit reports to www.thecomplianceengine.com