

2019-2029 SPU Contractor Solid Waste Trucks

Truck Type	Containers serviced	Wheel Base: steer axle to front drive axle	Wheel Base: steer axle to rear drive axle	Empty Weight (lbs)	Gross Weight (lbs)	Front axle GVW (lbs)	Drive Axle GVW (lbs)	Height	Width	Length	MINIMUM Turning Radius	Required vertical clearance for service
LAV (limited-access vehicle; a non-standard service option reserved only for extremely limited conditions)	2yd or smaller dumpsters; uncompacted materials	176"	N/A	24,000	32,000	12,000	20,000	11.5'	9.2'	28'	28'	12'
REL (rear-load)	2yd or smaller dumpsters; uncompacted materials	184"	238"	34,500	58,000	20,000	38,000	13.5'	10.1'	35'	35'	14'
FEL (front-load)	3 -8 yd dumpsters; uncompacted or compacted materials.	184"	238"	35,840	58,000	20,000	38,000	13.5'	10.1'	35'	35'	24'
Side-load (residential only)	Plastic carts only	200"	254"	35,160	58,000	20,000	38,000	13.5'	10.1'	35'	35'	16'
Roll-off	10yd+ roll-off dumpsters only; compacted or uncompacted materials.	200"	254"	31,340	60,000	20,000	40,000	10'	10.1'	35'	35'	14'

Notes:

SDOT-approved hammerhead turnarounds can accommodate safe maneuvering for solid waste trucks.

Trucks may NOT back up more than 50'

Trucks do NOT back out onto streets

Forks for front-load trucks add 6' to length of truck during service