

The City of Seattle

# Pioneer Square Preservation Board

Mailing Address: PO Box 94649, Seattle WA 98124-4649 Street Address: 600 4th Avenue, 4th Floor

PSB 104/24

### Staff REPORT

for ARC meeting April 24, 2024

Board Members Please Note: The citations from the District Ordinance, Rules for the Pioneer Square Preservation District, and Secretary of the Interior's Standards listed below are for your consideration in addition to any other citations you find relevant in considering each application.

## 042424.31 Triangle Building

553 1st Ave S

Proposed rehabilitation of the building

Staff report: The Board saw this at a briefing on October 4, 2023. The Board asked for some alternatives to be considered for the size and shape of the stair penthouse but generally supported the project. Staff noted that a modification to the setbacks was going to be necessary because of the size and shape of the building so the Board should be clear about their reasons for the modification and the attempt to make it minimally visible.

Code Citations:

Seattle Municipal Code

23.66.030 Certificates of Approval required

A. Certificate of approval required. No person shall alter, demolish, construct, reconstruct, restore, remodel, make any visible change to the exterior appearance of any structure, or to the public rights-of-way or other public spaces in a special review district, and no one shall remove or substantially alter any existing sign or erect or place any new sign or change the principal use of any building, or any portion of a building, structure or lot in a special review district, and no permit for such activity shall be issued unless a certificate of approval has been issued by the Department of Neighborhoods Director.

23.66.140 Height

"Printed on Recycled Paper"

- C. Rooftop features and additions to structures
- The height limits established for the rooftop features described in this Section 23.66.140 may be increased by the average height of the existing street parapet or a historically substantiated reconstructed parapet on the building on which the rooftop feature is proposed.
- 3. The setbacks required for rooftop features may be modified by the Department of Neighborhoods Director, after a sight line review by the Preservation Board to ensure that the features are minimally visible from public streets and parks within 300 feet of the structure.
- 4. Height limits for rooftop features
  - b. For existing structures, open railings, planters, clerestories, skylights, play equipment, parapets, and firewalls may extend up to 4 feet above the roof of the structure or the maximum height limit, whichever is less. For new structures, such features may extend up to 4 feet above the maximum height limit. No rooftop coverage limits apply to such features regardless of whether the structure is existing or new.
  - c. Solar collectors, excluding greenhouses, may extend up to 7 feet above the roof of the structure or the maximum height limit, whichever is less, with unlimited rooftop coverage, provided they are a minimum of 10 feet from all lot lines. For new structures, solar collectors may extend up to 7 feet above the maximum height limit, except as provided in subsection 23.66.140.C.4.j.1, and provided that they are a minimum of 10 feet from all lot lines.
  - d. The following rooftop features may extend up to 8 feet above the roof or maximum height limit, whichever is less, if they are set back a minimum of 15 feet from the street and 3 feet from an alley. They may extend up to 15 feet above the roof if set back a minimum of 30 feet from the street. A setback may not be required at common wall lines subject to review by the Preservation Board and approval by the Department of Neighborhoods Director. The combined coverage of the following listed rooftop features shall not exceed 25 percent of the roof area:
  - 1) Solar collectors, excluding greenhouses;
  - 2) Stair and elevator penthouses;
  - 3) Mechanical equipment;

#### III. GENERAL GUIDELINES FOR REHABILITATION AND NEW CONSTRUCTION

In addition to the Pioneer Square Preservation District Ordinance and Rules, The Secretary of the Interior's Standards for Rehabilitation with Guidelines for Rehabilitating Historic Buildings, and the complete series of Historic Buildings Preservation Briefs developed by the National Park Service shall serve as guidelines for proposed exterior alterations and treatments, rehabilitation projects, and new construction. (7/99)

Rehabilitation is defined as the act or process of making possible a compatible use for a property through repair, alterations, and additions while preserving those portions or features which convey its historical, cultural, or architectural values. (7/99) In considering rehabilitation projects, what is critical is the stabilization of significant historical detailing, respect for the original architectural style, and compatibility of scale and materials.

The following architectural elements are typical throughout the District and will be used by the Board in the evaluation of requests for design approval:

- A. <u>Site</u>. The property line is the line of the building mass. Street facades are uniformly located at the front property lines, thus there is a strong street edge definition. Building cornices, bay windows and ornament project beyond the main wall surface of some facades.
- B. <u>Design</u>. Building design is generally typified by horizontal divisions which create distinctive base and cap levels. Facades may also be divided vertically by pilasters or wide piers which form repetitive window bays. Street facades are also distinguished by heavy terminal cornices and parapets, ornamental storefronts and entrance bays and repetitive window sizes and placement.
- C. <u>Building materials</u>. The most common facing materials are brick masonry and cut or rusticated sandstone, with limited use of terra cotta and tile. Wooden window sash, ornamental sheet metal, carved stone and wooden or cast iron storefronts are also typically used throughout the District. Synthetic stucco siding materials are generally not permitted. (7/99)
- D. <u>Color</u>. Building facades are primarily composed of varied tones of red brick masonry or gray sandstone. Unfinished brick, stone, or concrete masonry unit surfaces may not be painted. Painted color is typically applied to wooden window sash, sheet metal ornament and wooden or cast iron storefronts. Paint colors shall be appropriate to ensure compatibility within the District. (7/99)

#### VIII. MECHANICAL SYSTEMS

The preferred location for mechanical systems is in the building interior. In cases where locating systems in the interior is not possible, exterior mechanical systems equipment, including but not limited to air conditioning units, compressors, boilers, generators, ductwork, louvers, wiring and pipes, shall be installed on non-primary building facades and/or roof tops. Mechanical equipment shall be installed in such a manner that character-defining features of the building are not radically changed, damaged, obscured, or destroyed. Screening and/or painting of equipment may be required to diminish negative visual impacts.

## XX. RULES FOR TRANSPARENCY, SIGNS, AWNINGS AND CANOPIES

## E. AWNINGS AND CANOPIES

Awnings and canopies are structures attached to buildings above storefront windows and entrances to provide weather protection.

Awnings are light-weight structures constructed of metal framing with fabric or vinyl covering. Canopies are heavier, more permanent structures constructed of rigid materials such as metal or metal framing with glass. (7/99) Those buildings wishing to use awnings or canopies shall adhere to the following requirements:

- Awnings shall be sloped, rather than bubble type. No writing may be
  placed on the sloping portion of the awning. (12/94) Scalloped or cut-out
  valances are not acceptable, nor are side panels. (8/93) Return of valances
  on awnings shall be permitted, but no signage of any kind shall be
  permitted on valance returns.
- 2. Shiny, high-gloss awning materials are not permitted. Retractable awnings of a through color are preferred, i.e., the underside is the same color as the exposed face. Awning colors shall be subdued to ensure compatibility with the character of the District. (7/03)
- 3. Canopies that are compatible in design, scale, materials, color, details, and method of attachment with the building and that do not display a false historical appearance are permitted. (7/03)
- 4. Awnings and canopies covering more than one story are not allowed. Distinctive architectural features shall not be covered, nor shall installation damage the structure.
- 5. Awnings and canopies must serve a functional purpose, and therefore shall project a minimum of five (5) feet horizontally. (7/03)
- 6. Internally illuminated awnings or canopies are not permitted. Neon is not allowed on awnings or canopies. (7/03)

## **Secretary of Interior's Standards**

- 1. A property will be used as it was historically or be given a new use that requires minimal change to its distinctive materials, features, spaces and spatial relationships.
- 2. The historic character of a property will be retained and preserved. The removal of distinctive materials or alteration of features, spaces and spatial relationships that characterize a property will be avoided.
- 3. Each property will be recognized as a physical record of its time, place and use. Changes that create a false sense of historical development, such as adding conjectural features or elements from other historic properties, will not be undertaken.
- 4. Changes to a property that have acquired historic significance in their own right will be retained and preserved.
- 5. Distinctive materials, features, finishes, and construction techniques or examples of craftsmanship that characterize a property will be preserved.
- 6. Deteriorated historic features will be repaired rather than replaced. Where the severity of deterioration requires replacement of a distinctive feature, the new feature will match the old in design, color, texture and, where possible, materials. Replacement of missing features will be substantiated by documentary and physical evidence.
- 7. Chemical or physical treatments, if appropriate, will be undertaken using the gentlest means possible. Treatments that cause damage to historic materials will not be used.
- 9. New additions, exterior alterations, or related new construction will not destroy historic materials, features, and spatial relationships that characterize the property. The new work will be differentiated from the old and will be compatible with the historic materials, features, size, scale and proportion, and massing to protect the integrity of the property and its environment.
- 10. New additions and adjacent or related new construction will be undertaken in such a manner that, if removed in the future, the essential form and integrity of the historic property and its environment would be unimpaired.

Issued: April 18, 2024

Genna Nashem
Pioneer Square Preservation Board Coordinator