PART 1 - GENERAL

1.01 WARRANTY:

A. Provide manufacturer's standard warranty for all hardware.

PART 2 - PRODUCTS

2.01 HINGES:

A. Stanley FBB 199 for 'high use' interior and exterior doors. Use NRP hinges for out swinging entry or exit doors.

2.02 CYLINDRICAL LOCKSETS:

A. General: Best '93K' Series. (NO substitutions).

B. Offices: Best 93K7AB.

C. Custodial Closets and Mechanical Rooms: Best 93K7D.

D. Multipurpose Rooms, Classrooms and Storerooms: Best 93K7R.

E. Family Changing/ADA Unisex Interior Restroom: Best 93K7T.

2.03 MORTISE LOCKSETS:

A. General: Best '35H' Series (or) Corbin Russwin ML2000 Series.

B. Offices: Best 35H7E (or) Corbin-Russwin ML2051.

C. Custodial Closets, Mechanical Rooms: Best 35H7EW (or) Corbin-Russwin ML2057

D. Multipurpose Rooms, Classrooms: Best 35H7J (or) Corbin-Russwin ML2055.

E. Storerooms: Best 35H7J (or) Corbin-Russwin ML2055 for handle and latch style (or) Best 35H7P (or) Corbin-Russwin ML2013 (for deadbolt with no handle).

2.04 TUBULAR DEADBOLTS:

A. Best 83T Series. (No substitutions).

B. Kitchens: Best 83T7K

C. Interior and exterior Restrooms (except Family Changing/ADA Unisex): Best 83T7S)

2.05 MORTISED DEADBOLTS (if accepted):

A. Best 38H (or) Corbin-Russwin DL4000.

2.06 LOCKS:

A. All cores shall be from "Best Access Systems", 18401 East Valley Highway, Park 184, Bldg. 2, Renton, WA, 98032, Ph. 425-251-6001. (No substitutions shall be accepted).

B. All keyed cylinders shall match Seattle Parks and Recreation (SPR) Standard (Figure 8 cores).

C. All locks shall be keyed into the established master key system for the SPR.

D. The Engineer, in conjunction with the Best Access System's Representative, shall determine keying arrangement.

E. All cores shall be Best (Figure 8) design for key control.

F. Cabinet and Desk Drawer locks: Best (Figure 8) 5L Series latch bolts or deadbolts rim mounted locks (or) Best 1E7E4 slabbed cabinet mortised cylinders.

G. All cylinders on all locking devices must accept Best (Figure 8) cores.

2.07 EXIT DEVICES:

A. Exit devices shall be Von Duprin 98/99 Series. (No substitutions).

B. Von Duprin 22 Series (or) Corbin-Russwin ED 8000 (for low traffic areas, such as back door to garbage area etc.).

C. On Storefront or Entrance Systems, use Von Duprin, or approved equal.

2.08 DOOR CLOSERS:

A. LCN 4041, or approved equal.

B. Corbin-Russwin 2400 Series or approved for Low Traffic Areas.

2.09 PUSH PULL AND KICK PLATES:

A. Finish shall be US-26 D or 33.

2.10 THRESHOLDS AND WEATHERSTRIPPING:

A. Pemko, or approved equal.

2.11 PADLOCKS:

A. All padlocks shall be Best padlocks.

PART 3 - EXECUTION

3.01 Any 1E Series Cam locks shall be installed such that the cylinder will not rotate in its hole (that is, the hole shall be routed to the same shape as the cylinder).

END OF SECTION